



Ø \_\_\_\_\_ PERFORATED ADS N-12 PIPE

ADS DRAINGUARD FILTER FABRIC (PERVIOUS BARRIER) AROUND ALL SIDES OF TRENCH (TOP, BOTTOM, & SIDES)

W

MIN.

H

TOP OF GRADE VARIES TO MATCH FINISH GRADE ELEV.

TOP OF TRENCH ELEV.

PIPE INVERT ELEV.

BOTTOM OF TRENCH ELEV.

\_\_\_\_\_ ' WIDE x \_\_\_\_\_ ' LONG TRENCH.  
 \_\_\_\_\_ C.F. TOTAL STORAGE VOLUME  
 PROVIDED IN PIPES & AGGREGATE

AGGREGATE TO COMPLY W/FDOT SPECIFICATIONS FOR COARSE AGGREGATE SIZE NUMBER 5 (1" TO 1/2"). NO LIMESTONE, DOLOMITES, OR SANDSTONES SHALL BE USED

**NOTE:**  
 CALCULATION TO BE PROVIDED FOR THE TOTAL STORAGE VOLUME OF EXFILTRATION TRENCH STORAGE.

2  


---

C-2
EXFILTRATION  
TRENCH DETAIL  
 N.T.S.