
The Enclosed Document Is Provided For Your Convenience.

Please Email ALL Questions: <u>MailTo:ContractAdministration@TampaGov.net</u>

Please Let Us Know If You Plan To Bid

City of Tampa Contract Administration Department 306 E. Jackson St. #280A4N Tampa, FL 33602 (813)274-8456



rd F. Curren Advanced Wastewater Treatment Plant Screen & Grit Building Nos. 1 & 2 Booster Pumps	W.O. 1000721
SCREEN & ORT BOILDING NOS. T & 2 BOOSTER TONPS	SHEET
COVER	1

GENERAL NOTES:


- THE CONTRACTOR SHALL COORDINATE HIS DAILY CONSTRUCTION, ACCESS, DELIVERY, STORAGE AND 1. OTHER SIMILAR ACTIVITIES WITH THE ENGINEER AND AWTP PERSONNEL. THE FUNCTION OF THE AWTP SHALL NOT BE COMPROMISED AT ANY TIME.
- EFFLUENT WATER FOR THE SCREEN AND GRIT BUILDING NUMBER ONE (# 059) IS PROVIDED 2. THROUGH THIS SCREEN AND GRIT BUILDING NUMBER TWO (# 005). THEREFORE IT IS EXTREMELY IMPORTANT THAT ANY SERVICE DISRUPTION IS KEPT TO THE MINIMUM.
- ANY PLANNED SERVICE INTERRUPTION TO THE NORMAL PLANT OPERATION SHALL BE MADE IN .3. WRITING VIA THE ENGINEER IN SUFFICIENT ADVANCE NOTICE TO ALLOW THE AWTP PERSONNEL TO APPROVE/DISAPPROVE THE REQUEST A MINIMUM OF 72 HOURS IN ADVANCE. INTERRUPTIONS SHALL BE KEPT TO THE MINIMUM DURATION AND FREQUENCY POSSIBLE.
- 4. EXISTING VALVES SHALL ONLY BE CLOSED OR OPENED BY AWTP PERSONNEL. LIKEWISE, ALL AWTP EQUIPMENT SHALL ONLY BE DE-ENERGIZED OR ENERGIZED BY AWTP PERSONNEL.
- LETTERING AND FLOW ARROWS SHALL BE STENCILED WITH PAINT. STICK-ON LABELS WILL NOT 5 BE ACCEPTED.
- POSSIBLE HIGH H2S GAS LEVELS MAY REQUIRE EXTRA SAFETY PRECAUTIONS AND/OR SPECIAL 6. EQUIPMENT BY THE CONTRACTOR.
- EXISTING DIMENSIONS AND ELEVATIONS ARE BASED ON THE BEST INFORMATION AVAILABLE. TRUE 7. DIMENSIONS AND ELEVATIONS SHALL BE DETERMINED IN THE FIELD, BY THE CONTRACTOR, PRIOR TO LAYOUT AND SHOP DRAWING SUBMITTALS.
- SHOP DRAWINGS SHALL BE SUBMITTED AND APPROVED BY THE CITY FOR ALL PROPOSED ITEMS. 8. ALL SUBMITTALS AND SHOP DRAWINGS SHALL BE ORIGINALS OR HIGH QUALITY COPIES (EASILY READABLE). NO FAXED SHEETS OR POOR QUALITY COPIES WILL BE ACCEPTED FOR SUBMITTAL REVIEW.
- CONTRACTOR IS RESPONSIBLE FOR MEETING ALL FEDERAL, STATE AND LOCAL GOVERNMENT 9. REGULATIONS IN REGARDS TO WORKING IN CONFINED SPACES.
- 10. UNLESS OTHERWISE INDICATED, CHEMICAL ANCHORS SHALL BE HILTI HIT-HY 150 MAX ANCHORING SYSTEM WITH TYPE 316 STAINLESS STEEL THREADED RODS, OR EQUAL.
- 11. OSHA STANDARD SAFETY EQUIPMENT SUCH AS SAFETY HARNESSES, GAS MONITORS, LOWER EXPLOSION LIMIT (LEL) DETECTORS, BREATHING APPARATUS, ETC., SHALL BE UTILIZED WHERE THE WORK DICTATES THEIR USE.
- 12. CONTRACTOR SHALL COORDINATE ALL CONSTRUCTION ACTIVITIES WITH CONTRACT ADMINISTRATION PERSONNEL AND TREATMENT PLANT OPERATORS.
- 13. THE CONSTRUCTION SITE SHALL BE MAINTAINED IN AS NEAT AND ORDERLY CONDITION AS POSSIBLE DURING CONSTRUCTION OPERATIONS. SITE SHALL BE SECURED WITH TEMPORARY FENCING AND STRUCTURES DURING HOURS WHEN CONTRACTOR IS NOT PRESENT TO ENSURE SAFETY OF CITY EMPLOYEES AND THE PUBLIC.
- 14. CONTRACTOR SHALL RESTORE ALL STRUCTURES, PIPES OR EQUIPMENT THAT MAY HAVE BEEN DAMAGED DURING CONSTRUCTION TO ITS ORIGINAL CONDITION OR BETTER.
- 15. ALL METAL SURFACES THAT COME IN CONTACT WITH CONCRETE SHALL RECEIVE TWO COATS OF COAL TAR EPOXY APPLIED TO THE METAL SURFACE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.

- 16. AREAS OF CONCRETE FLOOR/WALL THAT ARE DISTURBED SHALL BE REFINISHED TO PROVIDE A SMOOTH CONCRETE SURFACE.
- 17. NORMAL WORKING HOURS SHALL BE WEEKDAYS FROM 7:30 AM TO 4:00 PM UNLESS OTHERWISE APPROVED BY THE ENGINEER.
- 18. TESTING OF THE NEW INSTALLATIONS WILL BE ACCOMPLISHED BY OPERATING EACH PROJECT LOCATION FOR A MINIMUM TWO DAYS - 24 HOUR PERIODS (ONE DAY FOR EACH PUMP) DURATION AND OBSERVING FOR ANY LEAKS OR MALFUNCTION. SHOULD ANY PROBLEMS OCCUR DURING TESTING PERIOD, THE PROBLEM MUST BE RECTIFIED AND THE PUMP SYSTEM RETESTED.
- 19. CONTRACTOR SHALL VERIFY QUANTITIES OF ALL NECESSARY PIPES, REDUCERS, FITTINGS, SUPPORTS. AND ANY MISCELLANEOUS BRACKETS.
- 20. CONTRACTOR SHALL TAKE ALL PRECAUTIONARY MEASURES NECESSARY TO PROTECT EXISTING STRUCTURES AND EQUIPMENT FROM ANY DAMAGE.
- 21. ALL HARDWARE, STRAPS, SUPPORTS, ETC., SHALL BE 316 STAINLESS STEEL.
- 22. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE FLORIDA BUILDING CODE 5TH EDITION 2014, AND CHAPTER 5 OF THE CITY OF TAMPA CODE.
- 23. THE FOLLOWING PROPOSED PUMPS SHALL BE INSTALLED IN THE SCREEN AND GRIT BUILDING #1. PROPOSED PUMPS ARE PENTAIR AURORA PUMPS, MODEL 3804 10HP PUMPS. PROPOSED PUMPS SHALL BE 3-INCH DIAMETER INLET AND 2.5-INCH OUTLET TO PRODUCE 300 GPM @ 80' TDH.
- 24. THE FOLLOWING PROPOSED PUMPS SHALL BE INSTALLED IN THE SCREEN AND GRIT BUILDING #2. PROPOSED PUMPS ARE PENTAIR AURORA PUMPS, MODEL 340 7.5HP PUMPS. PROPOSED PUMPS SHALL BE 2.5" DIAMETER INLET AND 2" OUTLET TO PRODUCE 160 GPM @ 80' TDH.
- 25. GATE VALVES SHALL BE KENNEDY. RESILIENT WEDGE GATE VALVE. NON-RISING STEM OR APPROVED EQUAL. ALL GATE VALVES SHALL BE PROVIDED WITH HAND WHEELS.
- 26. CHECK VALVES SHALL BE APCO RUBBER FLAPPER SWING CHECK VALVES, SERIES 100. THIS EQUIPMENT IS A STANDARDIZED ITEM AT THIS FACILITY AND NO "OR EQUAL" SUBMITTALS WILL BE CONSIDERED.
- 27. ALL DIP PIPE AND FITTING SHALL BE CLASS 53 WITH PROTECTO 401 INTERIOR COATING AND PAINTED EXTERIOR.
- 28. PLUG VALVES SHALL BE DEZURIK. PEF 100% PORT. ECCENTRIC PLUG VALVES OR APPROVED EQUAL. ALL PLUG VALVES SHALL BE PROVIDED WITH HAND WHEELS.
- 29. ALL HARDWARE. PIPE SUPPORTS. ETC. SHALL BE 316 STAINLESS STEEL.
- 30. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH FLORIDA BUILDING CODE 5th EDITION 2014, & CHAPTER 5 OF THE CITY OF TAMPA CODE.

PROJECT SCOPE:


FURNISH AND PROVIDE ALL LABOR, MATERIALS, AND EQUIPMENT TO INSTALL (2) 10 Hp AND (2) 7.5 Hp BOOSTER PUMPS INCLUDING ASSOCIATED ACCESSORY EQUIPMENT, VALVE ASSEMBLIES, ELECTRICAL CONNECTIONS AND APPURTENANCES.

	No.	DATE	REVISIONS	DES: MS	CITY of TAMPA	Howard F. Curren Advanced Wastewater Treatment Plant Screen & Grit Building Nos. I & 2 Booster Pumps	W.O. 1000721
	3			DRN: RS	$O_{II} = O_{II} P_{A}$	BUILDING NOS. I & Z DUUSTER FUMPS	SHEET
JACINTO CARLOS FERRAS, P.E. #49454 DESIGN DIVISION HEAD	2			СКD:	HOWARD F. CURREN	LOCATION MAP AND INDEX	2
WASTEWATER DEPARTMENT	1			DATE: 3/20/17	ADVANCED WASTEWATER TREATMENT PLANT		




	Sheet Index
Number	Sheet Title
N AND GRIT	GENERAL
	COVER
	NOTES
	LOCATION MAP AND INDEX
N AND GRIT	BLDG. NO. 1
	BUILDING PLAN
	EXISTING FLOOR PLAN DEMOLITION
	EXISTING FLOOR PLAN - PICTURES
	PROP. BOOSTER PUMPS & SUCTION PIPING
	PROP. BOOSTER PUMPS & DISCHARGE PIPING
	DETAILS A & B
N AND GRIT	BLDG. NO. 2
	BUILDING PLAN
	EXISTING FLOOR PLAN - PICTURES
	PROP. BOOSTER PUMP & SUCTION PIPING
	PROP BOOSTER PUMPS & DISCHARGE PIPING
	DETAILS
N AND GRIT	DETAILS
	TYPICAL DETAILS
RICAL	
	ELECTRICAL LEGEND
	DRAWING INDEX AND GENERAL NOTES
	SCOPE OF ELECTRICAL WORK
	BUILDING NO. 1 FLOOR PLAN
	BUILDING NO. 1 ELECTRICAL SITE PLAN
	BUILDING NO. 1 GRIT PUMPING STATION NO. 3 FLOOR PLAN
	BUILDING NO. 1 AND NO. 2 VFD ELEVATION
	TYPICAL VFD WIRING DIAGRAM
	VFD PARAMETERS
	PIPING AND INSTRUMENTATION DIAGRAM
	VFD CONTROLS SCHEDULE
	BUILDING NO. 2 FLOOR PLAN
	BUILDING NO. 2 ELECTRICAL SITE PLAN
	BUILDING NO. 2 MCC-21 DETAILS

w.o. 100072*°* BUILDING NOS. 1 & 2 BOOSTER PUMPS SHEET 3 LOCATION MAP AND INDEX



0' 77B ŝ





=XISTING CONDITIONS - NORTII -- I -TII - KING -- T



-XISTING CONDITIONS - -- I - KING -- T

SCREEN & GRIT BUILDING NO. I
EXISTING FLOOR PLAN-PICTURES


	No.	DAT_	R_VISIONS	D_S: MS	CITY OF TAKE	Howard F. Curren Adva Buil
J- INTO C- LOS _RR #49454 D_SIGN DIVISION H_ - T_W-T_R D_P- \TM_NT	3 2 1			DRN: RS CKD: DAT <u>=</u> : 3/20/17	$CTTT OT TAMP_{4}$ wastewater department	SCREEN EXISTING


TPB017-006


KING NORTII-- T


-XISTING CONDITIONS - NORTII -


DVANCED WASTEWATER TREATMENT PLANT SCREEN & GRIT
BUILDING NOS. I & 2 BOOSTER PUMPSW.O.1000721BUILDING NOS. I & 2 BOOSTER PUMPSSH11EN AND GRIT BLDG. NO. 1GG FLOOR PLAN - PICTURES6












ss1s -- 1

User: Layou

бмр





_XISTING CONDITIONS – LOOKING NORTHW_ST



-XISTING CONDITIONS - LOOKING W-ST



±XISTING CONDITIONS – LOOKING NORTH





=XISTING CONDITIONS - LOOKING NORTH=- T


SCREEN AND GRIT BUILDING NO. 2)
EXISTING FLOOR PLAN - PICTURES	ò
NTC	

V.	Т.	S.	


	No.	DAT_	R_VISIONS	D_S: MS	CITY OF TAKE	HOWARD F. CURREN ADV
	3			DRN: RS	CITY OI IAMPA	B
J- INTO C-\LOS _RR #49454 D_SIGN DIVISION H_	2			CKD:	WASTEWATER DEPARTMENT	SCREE
- T=W-T=R D=P-\TM=NT	1			DAT <u>-</u> : 3/20/17		EXISTINC







User sats Draving Hernes Koj Wastehlicher Projecte) (Hew Soreen and Ort Building Booster Pump Addition (Deusja (Plans) (Drating) DMC) SCHEDN & Cert BLDS, NO. 2 PHCP BOOSTER PUMPS,



CKD: __


DAT_: 3/20/17

WASTEWATER DEPARTMENT


D=T-ILS.dwg	
ps- r Pump -ddi'ion\Design\Plans\Dra 'ing\DWG\SCRN & GRIT BLDG NO. 2	
ec- \New Screen and Gri- nilding Bou	_UNI.CTB
a- r Projec-	ств – _тоsн
K:\Was-	. — 2:36pm (
g Name:	2017 -
Drawin	Mar 27,
User: ss1s 1	Layou Mar 27, 2017

J- INTO C-\LOS =RR- .=. #49454 2 D=SIGN DIVISION H= - T=W-T=R D=P-\TM=NT 1

. Curren Advanced Wastewater Treatment Plant Screen & Grit	W.O. 1000721
BUILDING NOS. 1 & 2 BOOSTER PUMPS	SH <u></u> T
SCREEN AND GRIT BLDG. NO. 2	5HEET 1 /
DETAILS	4



SECTION VIEW - STAINLESS STEEL STANCHION SADDLE SUPPORT N.T.S.






N.T.S.

N L							
		No. DAT-	R_VISIONS	D_S: MS		HOWARD F. CURREN ADVANCED WASTEWATER TREATMENT PLANT SCREEN & GRIT	W.O. 1000721
2		3		DRN: RS	C_{1TY} of $T_{AMP_{A}}$	BUILDING NOS. 1 & 2 BOOSTER PUMPS	SH <u></u> T
no	J- INTO C- ∖LOS _RR <u>-</u> . #49454 D_SIGN DIVISION H_	2		CKD:	WASTEWATER DEPARTMENT	SCREEN AND GRIT DETAILS	15
<i>λ</i> 07	- T=W-T=R D=P-\TM=NT	1		DAT_: 3/20/17	WA THWATHY DELANIMENT	TYPICAL DETAILS	

C GOUNDARY LICETRODE CONDUCTOR CONDUCT STUDE OUT AND CAP CONDUCTION BOX CONDUCTION CONDUCTION BOX CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION CONDUCTION		ONDUIT RUN CONCEALED IN FLOOR OR SLAB ROUNDING ELECTRODE CONDUCTOR ONDUIT STUB OUT AND CAP ROUND ROD JNCTION BOX JNCTION BOX WITH FLEXIBLE CONNECTION RANSFORMER, 480V INDICATED PRIMARY VOLTAGE, 20/240V INDICATES SECONDARY VOLTAGE, 15 KVA EPRESENTS POWER RATING, AND 1* INDICATES NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	5 0 0 0 0 0 0 0 0 0 0 0 0 0	TRANSFER SWITCH ELECTRIC PANELBOARD DISCONNECT OR SAFETY SWITCH FLOAT SWITCH. CLOSES ON HIGH LEVEL.	B WALLPACK LIGHT FIXTURE. LETTER DESIGNATES FIXTURE TYPE. REFER TO FIXTURE SCHEDULE. Image: Construct and the state of t	SECTION SCALE : 1/4" = SHEET NUM WHERE SECTIO
Image: Section of the section of th	$\begin{array}{c} & & G \\ & & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ &$	ROUNDING ELECTRODE CONDUCTOR ONDUIT STUB OUT AND CAP ROUND ROD JNCTION BOX JNCTION BOX JNCTION BOX WITH FLEXIBLE CONNECTION RANSFORMER, 480V INDICATED PRIMARY VOLTAGE, 20/240V INDICATES SECONDARY VOLTAGE, 15 KVA EPRESENTS POWER RATING, AND 1* INDICATES NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	5 0 0 0 0 0 0 0 0 0 0 0 0 0	DISCONNECT OR SAFETY SWITCH FLOAT SWITCH. CLOSES ON HIGH LEVEL.	 EXIT LIGHT FIXTURE. REFER TO FIXTURE SCHEDULE. DUPLEX RECEPTACLE: 20A, 125VAC \$ SWITCH: SINGLE-POLE OR AS NOTED, 20A, 120/277VAC 	SCALE : 1/4" = SHEET NUN WHERE SECTIO
CONCUT STUD OUT AND CAP CONCUT STUD	$\begin{bmatrix} & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & $	ONDUIT STUB OUT AND CAP ROUND ROD JNCTION BOX JNCTION BOX JNCTION BOX WITH FLEXIBLE CONNECTION RANSFORMER, 480V INDICATED PRIMARY VOLTAGE, 20/240V INDICATES SECONDARY VOLTAGE, 15 KVA EPRESENTS POWER RATING, AND 1* INDICATES NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	(F) -56 -56-	DISCONNECT OR SAFETY SWITCH FLOAT SWITCH. CLOSES ON HIGH LEVEL.	DUPLEX RECEPTACLE: 20A, 125VAC SWITCH: SINGLE-POLE OR AS NOTED, 20A, 120/277VAC	SHEET NUN WHERE SECTIO
CONDUCTIVE DOUBLE SATURD CONDUCTIVE CONNECTION CONTROL DOUBLE SATURD CONNECTION BOX CONNECTION BOX CONNECTION CONNECTION BOX CONNECTION	$ \begin{array}{c} $	ROUND ROD JNCTION BOX JNCTION BOX WITH FLEXIBLE CONNECTION RANSFORMER, 480V INDICATED PRIMARY VOLTAGE, 20/240V INDICATES SECONDARY VOLTAGE, 15 KVA EPRESENTS POWER RATING, AND 1* INDICATES NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	(F) -56 -56-	DISCONNECT OR SAFETY SWITCH	\$ SWITCH: SINGLE-POLE OR AS NOTED, 20A, 120/277VAC	WHERE SECTIO
0 JUNCTION BOX Image: Second condition of the provided condit condit condition of the provided condition of the p	$\begin{array}{c} 0 \\ 480V \\ 15 \\ 120/240V \end{array} \begin{array}{c} 11 \\ 120/240V \end{array} \begin{array}{c} 11 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 120 \\ 1$	JNCTION BOX JNCTION BOX WITH FLEXIBLE CONNECTION RANSFORMER, 480V INDICATED PRIMARY VOLTAGE, 20/240V INDICATES SECONDARY VOLTAGE, 15 KVA EPRESENTS POWER RATING, AND 1* INDICATES NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	(F) -56 -56-	FLOAT SWITCH. CLOSES ON HIGH LEVEL.	20A, 120/277VAC	SHEET NUM
AUCTOR BOX AUCTOR A	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	JNCTION BOX WITH FLEXIBLE CONNECTION RANSFORMER, 480V INDICATED PRIMARY VOLTAGE, 20/240V INDICATES SECONDARY VOLTAGE, 15 KVA EPRESENTS POWER RATING, AND 1* INDICATES NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	(F) -050 -070-		EQUIPMENT TO BE REMOVED	SHEET NUM
490Y TRANSFORMER, AND INDUCATED PRIVATY OUTROE SHEET NUM 15 KVA, 14 TRANSFORMER, AND INDUCATED PRIVATY OUTROE TRANSFORMER VIA TORE, 15 KVA TRANSFORMER VIA TORE, 16 KVA TRANSF	$ \begin{array}{c} 480V \\ 15 \text{ KVA, 1*} \\ 120/240V \\ 3P \\ 30A \\ 0 \end{array} $	RANSFORMER, 480V INDICATED PRIMARY VOLTAGE, 20/240V INDICATES SECONDARY VOLTAGE, 15 KVA EPRESENTS POWER RATING, AND 1* INDICATES NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	-070-			SHEET NUM
15 KVA, 1* Image: Source and source of the source of	15 KVA, 1* 120 120/240V 12 3P 3OA 3OA O O O O O O O O	20/240V INDICATES SECONDARY VOLTAGE, 15 KVA EPRESENTS POWER RATING, AND 1* INDICATES NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	-	FLOAT SWITCH. CLOSES ON LOW LEVEL.		
SINGLE PHASE (FINEL PHASE))))) THERAL MARETIC CRCUIT REACKER WITH NUMBER OF POLES AND AMPERE RATING COMMENTION MAANTIC CRCUIT PREAKER WITH NUMBER OF POLES AND AMPERE RATING COMMENTION MAANTIC STARTER WITH CONTROL PARTY COMMENTION MAANTIC STARTER WITH CONTROL NUMBER FUNCTION NUMBER FUNCTION NU	3P 3OA CC	NGLE PHASE (THREE PHASE IF NOT INDICATED) HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	[WHERE SECTIC
3P THERMAL MARCHTC CRCUT DEBLACKER WITH NUMBER Image: constraint of the const		HERMAL MAGNETIC CIRCUIT BREAKER WITH NUMBER	1	NORMALLY OPEN (N.O.) CONTACT		
COMBINATION MACHETIC STARTER WITH CONTROL POWER TRANSFORMER (SZED FOR LOAD), LETTERS NDICATING PILOT LIGHT LETTER INDICATES COLOR N - REVERSING X - CONTACTOR SS - SOULD STATE SOFT START XX XX DEVICE DESCRIPTION HS HIGH LETTE, SWTCH HS LOW LEVEL SWTCH HS CONTROL SCHEMATIC WHEN ALLY COME HS SOTT STARTER SS PROSENT VOLTAGE SUPPRESSOR KT SS SOTT STARTER SS SOTT STARTER SS PROSENT VOLTAGE SUPPRESSOR KT SS SOTT STARTER SS SOTT STARTER SS PROSENT VOLTAGE SUPPRESSOR KT SS SOTT STARTER SS SOTT START	P(I JULIS AND ANN LIVE RATING	— // —	NORMALLY CLOSED (N.C.) CONTACT	WIRING INDICATED AS FOLLOWS:	DETAIL SCALE : 1/4"
POWER TRANSFORMER (SZED FOR LOAD). LETTERS N - NON-REVERSING N - NON-REVERSING N - NON-REVERSING S - CONTACTOR INDICATING PILOT LIGHT LETTER INDICATES COLOR OF LENS INDICATING PILOT LIGHT LETTER INDICATES COLOR OF LENS INDICATING PILOT LIGHT LETTER INDICATES COLOR OF LENS XXX - TOO-REVERSING S - CONTACTOR - TOO-REVERSING S - CONTACTOR - TOO-REVERSING OF LENS - TOO-REVERSING CLOSE NUMBER OF TOO-R	P(OMBINATION MAGNETIC STARTER WITH CONTROL	- <u>+</u> -	GROUND CONNECTION	'	SHEET NU
ZS - TWO-SPEED XX SS - SOLID STATE SOFT START Co DISCONNECT OR TOGGLE SWITCH VICE AND EXCEPTION		DICATE TYPE : – NON-REVERSING	R		LOR ISOLATED GR.	S
XXX XXX DESCRIPTION INDICATED) IN ALL POWER XXX HIGH LEVEL SWITCH HOA HOA LO LEAK DETECTION LLS LUS LUS LUS LUS LUS LOR LOCAL-OFF-REMOTE SS/B HIGH LEVEL SWITCH HOA LOCAL-OFF-REMOTE SS/S Output Output Output INDICATED) IN ALL POWER PUSH-BUTTON SWITCH SPRING OPEN. NUMBER OF CONTROL SCHEMATIC XXX HIGH LEVEL SWITCH HOA LOCAL-OFF-REMOTE SS/S Output Output Output INDICATED) IN ALL POWER PUSH-BUTTON SWITCH SPRING CONTACT. SUBJECT NO SWITCH SPRING CONTACT. CONTROL SCHEMATIC XXX DEVELOPMENTARY CIRCUIT OPENING PUSH-BUTTON SS/S NORMALLY CLOSED MOMENTARY CIRCUIT OPENING PUSH-BUTTON SWITCH SUBJECT NO SWITCH SS/S Output NORMALLY CLOSED MOMENTARY CIRCUIT OPENING PUSH-BUTTON SWITCH SUBJECT NO SWITCH SS/S Output Output NORMALLY CLOSED CONTACT. CONTROL SCHEMATIC XXX MOTOR FEMERATIVE SWITCH SS/S SOFT START OR BYPASS TS TRANSFERT VOLTAGE SUBGE SUPPRESSOR ZS Output IJMIT SWITCH NORMALLY CLOSED CONTACT. CONTACT OPENS WHEN ACTUATED XXX MOTOR FEMERATIVE SWITCH SWITCH Output TORQUE SWITCH NORMALLY CLOSED CONTACT. CONTACT OPENS WHEN ACTUATED XXX MOTOR FEMERATIVE SWITCH SWITCH Output Output NOTOR THERMAL SENSOR	/ с	S – TWO–SPEED – CONTACTOR	-00-	DISCONNECT OR TOGGLE SWITCH	3/4" C. UNLESS OTHERWISE NOTED AND EQUIPMENT	
LD LEAR DETECTION LLS LOW LEVEL SWITCH LOR LOCAL-OFF-REMOTE DOR LOCAL-OFF-REMOTE DOR LOCAL-OFF-REMOTE DOR LOCAL-OFF-REMOTE DOR B PUSH BUITON RTU REMOTE TERMINAL UNIT S/S START/STOP SELECTOR SWITCH SS B SOFT START OR BYPASS SS /B SOFT START OR BYPASS TEMPERATURE SWITCH TYSS TRANSIENT VOLTACE SURPERSSOR ZS POSTION SENSOR (LIMIT SWITCH) FUSE XX MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR (MOTOR	Н	LS HIGH LEVEL SWITCH	- - 00	PUSH-BUTTON SWITCH. SPRING OPEN. NUMBER ELECTRICAL CONTACTS ON SWITCH SHOWN ON	INDICATED) IN ALL POWER AND LIGHTING RACEWAYS.	
SS SOFT STARTER SS/B SOFT STARTER SS/B SOFT START OR BYPASS TS TEMPERATURE SWITCH TVSS TRANSIENT VOLTAGE SURGE SUPPRESSOR ZS POSTION SENSOR (LIMIT SWITCH) FUSE XX MOTOR VXX MOTOR SS/B SOFT STARTER SS/B SOFT START OR BYPASS TEMPERATURE SWITCH TORQUE SWITCH NORMALLY CLOSED CONTACT. CONTACT OPENS WHEN ACTUATED CONTACT OPENS WHEN ACTUATED SS/B SOFT START OR BYPASS TORQUE SWITCH NORMALLY CLOSED CONTACT. CONTACT OPENS WHEN ACTUATED SS/B SOFT START OR BYPASS TORQUE SWITCH NORMALLY CLOSED CONTACT. CONTACT OPENS WHEN ACTUATED SS/B SOFT START OR BYPASS TORQUE SWITCH NORMALLY CLOSED CONTACT. CONTACT OPENS WHEN ACTUATED SS/B SOFT START OR BYPASS TORQUE SWITCH NORMALLY CLOSED CONTACT. CONTACT OPENS WHEN ACTUATED	LI LL LC PI R	D LEAK DETECTION S LOW LEVEL SWITCH DR LOCAL-OFF-REMOTE B PUSH BUTTON TU REMOTE TERMINAL UNIT	- <u>o o</u> -	PUSH-BUTTON SWITCH. SPRING CLOSE. NUMBE OF ELECTRICAL CONTACTS ON SWITCH SHOWN	R	
Image: Signal and Sensor (Limit Switch) Image: Sensor (Limit Switch) Image: Switch NormalLy closed contact. Contact OPENS WHEN ACTUATED Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch NormalLy closed contact. Image: Switch Normal Normal Normal NormalLy closed con	S: S: T:	S SOFT STARTER S/B SOFT START OR BYPASS S TEMPERATURE SWITCH				
FUSE → ← MOTOR THERMAL SENSOR XX MOTOR PE PHOTOCELL	Z	S POSTION SENSOR (LIMIT SWITCH)	-00			
XX MOTOR PE PHOTOCELL		JSE	~ <u>~</u> ~	MOTOR THERMAL SENSOR		
	XX M	OTOR	PE	PHOTOCELL		
		HERMAL OVERLOAD	(s) -0/0-	SOLENOID VALVE		

Ē	WASTEWATER DEPARTMENT	2		CKD:	WASTEW
		1		DATE: 3/20/17	WASTEN

 $^{M}P_{A}$ U1 WATER DEPARTMENT



DRAWING IND	EX						
SHEET No.	SHEET TITLE						
E1	ELECTRICAL LEGEND						
E2	DRAWING INDEX AND GENERAL NOTES						
E3	SCOPE OF ELECTRICAL WORK						
E4	BUILDING No.1 FLOOR PLAN						
E5	BUILDING No.1 ELECTRICAL SITE PLAN						
E6	BUILDING No.1 GRIT PUMPING STATION No.3 FLOOR PLAN						
E7	BUILDING No.1 & No.2 VFD ELEVATION						
E8	TYPICAL VFD WIRING DIAGRAM						
E9	VFD PARAMETERS						
E10	PIPING AND INSTRUMENTATION DIAGRAM						
E11	VFD CONTROLS SCHEDULE						
E12	BUILDING No.2 FLOOR PLAN						
E13	BUILDING No.2 ELECTRICAL SITE PLAN						
E14	BUILDING No.2 MCC-21 DETAILS						

	GENERAL NOTES :
1.	CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR APPROVAL PRIOR TO PURCHASING EQUIPMENT OR COMMENC CONSTRUCTION.
2.	ALL CONDUCTORS SHALL BE STRANDED COPPER, #12 AWG MIN. WITH XHHW-2 INSULATION, UNLESS OTHERWIS
3.	VERIFY ALL MECHANICAL EQUIPMENT SIZES AND RATING PRIOR TO CONNECTING.
4.	FIELD VERIFY ALL EQUIPMENT LOCATIONS AND CONNECTIONS PRIOR TO COMMENCING CONSTRUCTION.
•	PLANS ARE DESIGNED IN ACCORDANCE WITH THE 5TH EDITION OF THE 2014 FLORIDA BUILDING CODE AND TH EDITION OF THE NATIONAL ELECTRICAL CODE. CONTRACTOR SHALL ENSURE THAT ALL ELECTRICAL WORK PERFO ADHERE TO THE SAME ACCORDANCE AND ALL APPLICABLE LOCAL ORDINANCES.
5.	ALL THREADED CONNECTIONS SHALL BE COATED WITH COPPER SHIELD ANTI-SEIZE COMPOUND MANUFACTURED & BETTS (T & B) OR EQUAL.
7.	ALL PANELS, DISCONNECTS, SWITCHES, AND EQUIPMENT COVERPLATES SHALL BE LABELED WITH NAMEPLATES. SHALL BE THREE-PLY PHENOLIC BLACK-WHITE-BLACK ENGRAVED THROUGH THE FIRST BLACK LAYER. LETTERIN 0.5 CM (3/16") MIN. EDGE OF NAMEPLATE SHALL BE BEVELED 45 DEG.
8.	ALL CONDUIT SHALL BE SUPPORTED AT MAXIMUM 5'-0" INTERVALS.
9.	ALL CIRCUITS SHALL HAVE A PROPERLY SIZED GROUNDING CONDUCTOR ROUTED INSIDE EACH CONDUIT WITH F CONDUCTORS.
10.	ALL CONDUCTOR LENGTHS SHALL BE CONTINUOUS, NO SPLICES OR CONDUCTOR TERMINATIONS SHALL BE PER UNLESS SPECIFICALLY DESIGNATED IN THE DRAWINGS.
11.	PROVIDE A MINIMUM OF $3'-6''$ CLEARANCE IN FRONT OF ALL ELECTRICAL EQUIPMENT IN ACCORDANCE WITH AF OF THE NEC.
12.	ALL FASTENING HARDWARE (SCREW, BOLTS, NUTS, ETC.) SHALL BE 316-STAINLESS STEEL. FASTENING HARDWA CONSTRUCTED OF FERROUS MATERIAL ARE NOT ACCEPTABLE.
13.	INTERIOR CONDUITS SHALL BE NON-COATED RIGID ALUMINUM CONDUIT, EXTERIOR, ABOVEGROUND CONDUIT SHALUMINUM CONDUIT WITH 40 MIL PVC COATING. BELOWGRADE CONDUIT SHALL BE SCHEDULE 80 PVC.
14.	ALUMINUM WATERTIGHT HUBS (MYERS HUBS) SHALL BE USED FOR CONNECTIONS TO CONTROL BOXES, ETC. M OUTDOORS, BELOW GRADE, OR IN WASHDOWN AREAS.
15.	A 316-STAINLESS STEEL CHANNEL ERECTOR SYSTEM SHALL BE USED TO SUPPORT ALL CONDUITS, BOXES, ET 316-STAINLESS STEEL MOUNTING HARDWARE.
6.	THE CONTRACTOR SHALL FIELD VERIFY EXISTING CONDITIONS AND MAKE ADJUSTMENTS AS NECESSARY TO EXEC PROPOSED INSTALLATIONS.
17.	ALL EXISTING INSTALLATIONS DENOTED ON THE DRAWINGS ARE FOR THE CONTRACTOR'S REFERENCE ONLY. AL INSTALLATIONS SHALL BE FIELD VERIFIED PRIOR TO SUBMITTING A BID AND PRIOR TO COMMENCING CONSTRUCT
18.	PULL BOXES SHALL BE INSTALLED AS NECESSARY TO FACILITATE WIRE PULLS AND AVOID EXCESSIVE PULLING WIRING. IN NO CASE SHALL CONDUIT LENGTHS EXCEED 150' OR THE EQUIVALENT OF FOUR QUARTER BENDS DEGREES TOTAL) WITHOUT A PULL BOX. PULL BOXES SHALL BE SIZED IN ACCORDANCE WITH ARTICLE 314 O
19.	ALL ELECTRICAL WORK SHALL BE PERFORMED WITHIN LATEST NEC AND CITY OF TAMPA/ HILLSBOROUGH COUN AND SHALL BE INSPECTED BY CITY OF TAMPA/ HILLSBOROUGH COUNTY ELECTRICAL INSPECTORS AS APPLICAB
20.	ALL ELECTRICAL COMPONENTS SHALL BE UL LISTED AND AS SPECIFIED, OR AS APPROVED BY THE ENGINEER. BUILDER SHALL BE UL-508A CERTIFIED AND A UL LABEL SHALL BE ATTACHED TO THE INSIDE OF THE ENCLOS
21.	ALL EXISTING CONDUIT TO BE REUSED SHALL BE CLEANED USING A SWAB. THE CONTRACTOR SHALL THEN RU PROPERLY SIZED RUBBER SLUG MANDREL THROUGH THE CONDUIT TO PROVE INTEGRITY PRIOR TO THE INSTALL ANY NEW CONDUCTORS.

ENAME		No.	DATE	REVISIONS	DES: RDK	CITY OF TAKE	Howard F. Curren Advai Buil
LE N	ROMAN D. KORCHAK, P.E. #42626 ELECTRICAL SECTION HEAD	3			DRN: RDK	CITY OF IAMPA	BUIL
	WASTEWATER DEPARTMENT	2			CKD:	WASTEWATER DEPARTMENT	
		1			DATE: 3/20/17	WASIEWAIEK DEFANIMENI	

NCING

VISE NOTED.

THE 2011 FORMED SHALL

ED BY THOMAS

5. NAMEPLATES RING SHALL BE

POWER

ERMITTED

ARTICLE 110

WARE

SHALL BE RIGID

MOUNTED

ETC. USE

KECUTE THE

ALL EXISTING UCTION.

IG TENSION ON IDS (360 I OF THE NEC.

UNTY CODES ABLE.

R. THE PANEL LOSURE.

RUN A ALLATION OF

nced Wastewater Treatment Plant Screen & Grit .ding Nos. I & 2 Booster Pumps	
GENERAL NOTES	sheet E2


SCOPI - + + TRICAL WORK - NISH - INST _QUIPM_NT, CONTROLS - INSTRUM_NT-TION - HOWN ON TH_ PL _SCRIB_D IN TH_ SP_CI-IC-TIONS. -. SP_CI-IC- / - x BUILDING #1 (059), GRIT PUMP ST-TION #3 (CL- I, DIVISION 1, GROUP D - x-- : 1. PROVID_ - INST- T_R PUMPS WBP-1 - -2. - H PUMP COMPRIS_S TH_ - ING: a.10 HP INDUCTION MOTOR b.SUCTION PR_SSUR_ TR- ITT_R c.DISCH-\G_ PR_SSUR_ TR- ITT_R d. "ON-O -" PUSHBUTTON ST-TION 2. RUN CONDUITS -TORS - NOM THE BOOSTER PUMPS TO THE ELECTRIC- NOOM - HOWN, SP_CI-I_D, - _QUIR_D. NOT_ TH-T CONCR_T_ P_N_TR-TIONS MUST B_ M _ TO INST- TH_ N_W CONDUITS. B. SP_CI-IC- / - \ BUILDING #1 (059), _L_CTRIC- \OOM (NON-CL- I-I_D - _- : 1. PROVID: - INST- IRCUIT BR:-K:R CUBICL:S 4: - \ :XISTING MOTOR CONTROL C::NT:R MCC-28. T_R PUMP V-\I _ -_QU_NCY DRIV_S V 2. PROVID: - INST-– HOWN, SP_CI-I_D, - _QUIR_D. 3. RUN CONDUITS - TORS - VOM MCC-28 TO V - HOWN, SP_CI-I_D -_QUIR_D. 4. RUN CONDUITS - NOMV - TO EXISTING SC - NTU - HOWN, SPECI-IED, - NEQUIRED. 5. PROGR - TO P_R- \M TH_ T- KS D_SCRIB_D IN TH_ PL- . C. SP_CI-IC- / - V BUILDING #2 (005), GRIT T- K L_V_L (CL- I, DIVISION 1, GROUP D - V_- : 1. PROVID: - INST- T_R PUMPS WBP-1 - -2. =- H PUMP COMPRISES TH: - ING: a.7.5 HP INDUCTION MOTOR b.SUCTION PR_SSUR_ TR- ITT_R c.DISCH-\G_ PR_SSUR_ TR- ITT_R d. "ON-O -" PUSHBUTTON ST-TION 2. RUN CONDUITS - TORS - NOM THE BOOSTER PUMPS TO THE ELECTRIC- NOOM - HOWN, SPECI-IED, - VEQUIRED. NOTE THET CONCRETE PENETRETIONS MUST BE M E TO INSTE THE NEW CONDUITS. D. SP_CI-IC- / - \ BUILDING #2 (005), _L_CTRIC- \OOM (NON-CL- I-I_D - _- : 1. PROVIDE - INST- IRCUIT BRE-KER CUBICLES 3D - LEXISTING MOTOR CONTROL C_NT_R MCC-21. 2. PROVID_ - INST-T_R PUMP V-\I _ -_QU_NCY DRIV_S V - HOWN, SP_CI-I_D, - _QUIR_D. 3. RUN CONDUITS - TORS - \OM MCC-21 TO V - HOWN, SP_CI-I_D -∖_QUIR_D. 4. RUN CONDUITS - VOMV - TO _XISTING SC - VTU - HOWN, SP_CI-I_D, - V_QUIR_D. 5. PROGR - TO P_R- M TH_ T- KS D_SCRIB_D IN TH_ PL- . L. INST- THE GROUND SYSTEM - HOWN, SPECI-IED - VEQUIRED. -. PROVID: - INST- T-INLESS STEEL CH EL ERECTOR SYSTEMS TO MOUNT - T -NCLOSUR_S, BOX_S, CONDUITS - TH_R _QUIPM_NT. G. _L_CTRIC- VK SH _ P_R- VM_D IN - VD _ WITH TH_ 2011 N-TION _L_CTRIC _ (N_C) - H- T_R 5 O- TH_ CITY O- T _.

	No.	DAT-	R=VISIONS	D_S: RDK		HOWARD F. CURREN ADVAN
ROMAN D. KORCHAK, P.1. #42626	3			DRN: RDK	CITY of TAMPA	Built
WAST_WAT_R D_PARTM_NT	2			CKD:	WASTEWATER DEPARTMENT	SCOPE
	1			DAT_: 3/20/17	WATEWATEN DELANIMENT	


ā


-IL-N

NCED WASTEWATER TREATMENT PLANT SCREEN & GRIT LDING NOS. I & 2 BOOSTER PUMPS	W.O. 1000721
E OF ELECTRICAL WORK	^{SH} T E3










FROM	то	COMMENTS
MCC28, 4E	VFD1	XHHW-2 CU
VFD1	WBP-1	XHHW-2 CU
AL "ON-OFF" SWITCH	VFD1	XHHW-2 CU
SS. TRANS PT1-S & -D	VFD1	BELDEN 9341
VFD1	EX. SCADA RTU	
VFD1	EX. SCADA RTU	XHHW-2 CU
MCC28, 8E	VFD2	XHHW-2 CU
VFD2	WBP-2	XHHW-2 CU
AL "ON-OFF" SWITCH	VFD2	XHHW-2 CU
SS. TRANS PT2-S & -D	VFD2	BELDEN 9341
VFD2	EX. SCADA RTU	
VFD2	EX. SCADA RTU	XHHW-2 CU

HOWARD F. CURREN ADVANCED WASTEWATER TREATMENT PLANT SCREEN & GRIT BUILDING NOS. I & 2 BOOSTER PUMPS



BUILDING NO. I, GRIT P.S. NO. 3 FLOOR PLAN



FILENAN


KEYED NOTES:

	NEW 480V, 10 HP VARIABLE FREQUENCY DRIVE (VFD) FOR NEW BOOSTER PUMP NO. 1. REFER ALSO TO SPECIFICATIONS.
2	NEW 480V, 10 HP VARIABLE FREQUENCY DRIVE (VFD) FOR NEW BOOSTER PUMP NO. 2. REFER ALSO TO SPECIFICATIONS.
3	PROVIDE AND INSTALL $1-5/8$ " x $1-5/8$ " 316 STAINLESS STEEL UNISTRUT. ALL MOUNTING HARDWARE SHALL BE 316 STAINLESS STEEL.
4	CONTRACTOR TO PROVIDE AND INSTALL $3-\#8$ XHHW-2 CU + 1-#10 XHHW-2 CU GND + 2-#12 XHHW-2 CU (MOTOR THERMALS) IN NEW 1" CONDUIT FROM NEW BOOSTER PUMP NO. 1 VFD TO NEW BOOSTER PUMP NO. 1 MOTOR.
5	CONTRACTOR TO PROVIDE AND INSTALL $2-#14$ XHHW-2 CU + $1-#14$ XHHW-2 CU GND IN NEW $3/4$ " CONDUIT FROM NEW BOOSTER PUMP NO. 1 VFD TO NEW LOCAL ON-OFF SWITCH LOCATED ADJACENT TO BOOSTER PUMP NO. 1 MOTOR.
6	PROVIDE AND INSTALL (1) CAT-5E CABLE FROM VFD1 TO EX. SCADA RTU FOR MODBUS COMMUNICATION.
7	CONTRACTOR TO PROVIDE AND INSTALL 10-#14 XHHW-2 CU + 1-#14 XHHW-2 CU GND IN NEW 1" CONDUIT FROM NEW BOOSTER PUMP NO. 1 VFD TO EXISTING RTU UNIT. 2-#14 FOR VFD FAULT, 2-#14 FOR VFD RUNNING, 2-#14 FOR LOW PRESSURE FEEDBACK, 4-#14 SPARES.
8	CONTRACTOR TO PROVIDE AND INSTALL $3-\#8$ XHHW-2 CU + $1-\#10$ XHHW-2 CU GND + $2-\#12$ XHHW-2 CU (MOTOR THERMALS) IN NEW 1" CONDUIT FROM NEW BOOSTER PUMP NO. 2 VFD TO NEW BOOSTER PUMP NO. 2 MOTOR.
(9	CONTRACTOR TO PROVIDE AND INSTALL $2-#14$ XHHW-2 CU + $1-#14$ XHHW-2 CU GND IN NEW $3/4$ " CONDUIT FROM NEW BOOSTER PUMP NO. 2 VFD TO NEW LOCAL ON-OFF SWITCH LOCATED ADJACENT TO BOOSTER PUMP NO. 2 MOTOR.
(10)	PROVIDE AND INSTALL (1) CAT-5E CABLE FROM VFD2 TO EX. SCADA RTU FOR MODBUS COMMUNICATION.
(11)	CONTRACTOR TO PROVIDE AND INSTALL 10-#14 XHHW-2 CU + 1-#14 XHHW-2 CU GND IN NEW 1" CONDUIT FROM NEW BOOSTER PUMP NO. 2 VFD TO EXISTING RTU UNIT. 2-#14 FOR VFD FAULT, 2-#14 FOR VFD RUNNING, 2-#14 FOR LOW PRESSURE FEEDBACK, 4-#14 SPARES.
(12)	CONTRACTOR TO PROVIDE AND INSTALL NEW CONDUIT CLAMPS AS REQUIRED.
(13)	EXISTING JUNCTION BOX. EXISTING DIMENSION BETWEEN JUNCTION BOXES IS APPROXIMATELY 51.5 INCHES. CONTRACTOR SHALL INSTALL NEW VFD'S IN BETWEEN EXISTING JUNCTION BOXES WHILE MAINTAINING REQUIRED CLEARANCES FOR VFD EXHAUST.
(14)	CONTRACTOR TO PROVIDE AND INSTALL 3-#8 XHHW-2 CU + 1-#10 XHHW-2 CU GND IN NEW 1" CONDUIT FROM NEW BOOSTER PUMP NO. 1 VFD TO EXISTING MCC NO. 28.
(15)	CONTRACTOR TO PROVIDE AND INSTALL 3-#8 XHHW-2 CU + 1-#10 XHHW-2 CU GND IN NEW 1" CONDUIT FROM NEW BOOSTER PUMP NO. 2 VFD TO EXISTING MCC NO. 28.''''
(16)	PROVIDE AND INSTALL (1) 1–1/2 PAIR BELDEN #3106A CABLE IN 3/4" CONDUIT FOR MEMOBUS/MODBUS COMMUNICATION.
(17)	PROVIDE AND INSTALL (2) 2C-TP-SHIELDED & (1) #14 GND IN 3/4" IN CONDUIT FOR PRESSURE TRANSDUCERS PT1S AND PT1D.
(18)	PROVIDE AND INSTALL (2) 2C-TP-SHIELDED & (1) $\#14$ GND IN 3/4" IN CONDUIT FOR PRESSURE TRANSDUCERS PT2S AND PT2D.

HOWARD F. CURREN ADVANCED WASTEWATER TREATMENT PLANT SCREEN & GRIT BUILDING NOS. I & 2 BOOSTER PUMPS

BUILDING No. I & 2, VFD ELEVATION

sheet **E7**



FILEN

No.	Name	Description	Val				
OPERATION MODE SELECTION							
b1-01	Frequency Ref. Sel. 1	Reference Source: HOA Keypad	0				
b1-02	Run Command Sel. 1 (Auto Mode)	Operator (HOA Keypad)	0				
b1-03	Stopping Method (H1-02)	Ramp to Stop	0				
b1-11	Run Delay at Stop	t= 30.0 sec	30				
	MULTI-FUNG	TION DIGITAL INPUTS					
H1-02	Term. S2 Func. Select	Drive Enable (Remote Stop)	6/				
H1-04	Term. S4 Func. Select	Ext. Fault- Mtr. Temp. (N.C.) Coast to Stop	2				
H1-05	Term. S5 Func. Select	Analog Input Selected	С				
		TION DIGITAL OUTPUTS					
H201	Term. M1-M2 Func. Sel.	VFD Running	0				
H2-02	Term. M3-M4 Func. Sel.	Feedback Signal "Low Press."	9				
H2-03	Term. MD-MF Func. Sel.	Automatic Mode	4				
	MULTI-FUNC	TION ANALOG INPUTS					
H3-14	Analog Input Term. Enable Selection	Terminals A2 & A3 Enabled	6				
H3-05	Term. A3 Level Select	Suction Feedback Level: 4-20mA	2				
H3-06	Term. A3 Func. Select	Suction Input / Feedback	2				
H3-07	Term. A3 Gain Setting	Suction Input Gain= 100%	100				
H3-08	Term. A3 Bias Setting	Suction Input Bias, 4mA= 0.0%	0.				
H3-09	Term. A2 Level Select	PID Feedback Level: 4-20mA	2				
H3-10	Term. A2 Func. Select	PID Feedback	E				
H3-11	Term. A2 Gain Setting	PID Feedback Gain= 100%	100				
H3-12	Term. A2 Bias Setting	PID Feedback Bias 4mA= 0.0%	0.				
	MEMOBUS	SETUP PARAMETERS					
H5-01	Drive Node Network Address	Booster P1 / Booster P2	1/				
	Н	MI DISPLAY					
o1-01	User Monitor Select	Last Monitor Scrolled= Output Volts	10				
o1-02	Power On Monitor	Frequency Reference	1				
o1-03	Display Unit Select	User Selected Units (o1-09)	3				
o1-06	2nd & 3rd L. Mon. Mode Sel.	3 User Selectable (o1-07 & o1-08)	1				
o1-07	2nd Line Mon. Mon. Sel.	Output Frequency	10				
o1-08	3rd Line Mon. Mon. Sel.	PID Feedback	19				
o1-09	Freq. Ref. Disp. Units	Frequency Reference Units= PSI	1				
o1-10	Display Unit Max. Value	150 PSI	15				
o1-11	Disp. Units Decimal	one decimal place	1				
o1-12	Home Help Text	default = enabled= 1	1				

	YASKAWA IQ10	000 VFD PROGRAMMING					
No.	Name	Description	Value				
PUMP PARAMETERS							
P1-01	Pump Mode	Memobus Network	3				
P1-02	System Units	PSI	1				
P1-03	Feedback Device Scaling	150 PSI	150.0				
P1-04	Start Level	-5.0 PSI	-5.0				
P1-05	Start Level Delay Time	Time= 5 sec.	5				
P1-08	Low FDBK Level	Low Level= 60 PSI	60.0				
P1-09	Low FDBK Delay Time	Delay= 10 sec	10.0				
P1-10	Low FDBK Selection	Display "Low FDBK" & Close D.O. H2-02= 97	1				
P1-11	High FDBK Level	High Level= 125 PSI	125.0				
P1-12	High FDBK Delay Time	Delay= 10 sec	10.0				
P1-13	High FDBK Selection	Display "High FDBK" Only	2				
P2-01	Sleep Level Type	Output Frequency	0				
P2-02	Sleep Level	Freq.= 30Hz	30.0				
P2-03	Sleep Delay Time	Time= 30 sec.	30				
P2-15	Sleep Auto Off	Disable	0				
	PUN	IP ADVANCED					
P4-10	Auto Mode on Power Loss	Enabled	1				
P4-17	Utility Start Delay	Time= 1 min	1.0				
	PUM	P HAND MODE					
P5-01	Hand Mode Ref. Source	P5-01 (Hand ref.)	1				
P5-02	Hand Reference 1	Freq.= 40Hz	40.0				
P5-03	Hand/Auto During Run Sel.	Enabled	1				
P5-04	Hand Key Func. Sel.	Hand Key Enabled	1				
	Net	twork Options					
P9-01	Lead Drive Selection	Next Available	0				
P9-02	Feedback Source	Analog > Network, Alarm	2				
P9-05	Lag Drive Mode	Turn Off	2				
P9-25	Highest Node Address	set to 3	3				
P9-50	Suction Pressure Source	Analog > Network, Alarm	2				
	PID CONTR	OLLER PARAMETERS					
Q1-01 / U1-01	PID Setpoint	Disch. Pressure Set point =85 PSI	85.0				
	SUCTION PRESSU	IRE CONTROLPARAMETERS					
Q5-01	Suction Press. Sel.	Suction Pressure (PSI)	1.0				
Q5-02	Suction Trans'r Scaling	Full Scale (20mA)= 150 PSI	1.0				
Q5-03	Suction Press. Setpoint	Setpoint= 50 PSI	50.0				
Q5-04	Min. Suction Pressure	Min. Press.= 30 PSI	30.0				
Q5-05							
Q5-06	Q5-06 Wake-Up Suction Press. Wake-Up Suction Press.= 50 PSI						
Q5-07	Suct. Press. Wake-Up Time	t= 2sec.	2.0				
Q5-08	Suct. Press. Min. Speed	Min Spd.= 40Hz	40.0				

NOTES:

OP-R-TION:

2.0P_R-TION:

THE INTENT IS TO REGULTE DISCH-GE PRESSURE - TION PRESSURE IN THE - ING M _R:

-.) WHEN THE SUCTION PRESSURE, ME- NED BY TR ER, IS E THE PROGR ED SUCTION PR_SSUR_ S_T POINT LOC-T_D IN R_GIST_R Q5-03, TH_ V- ILL R_GUL-T_ TH_ SP_LD O- TH_ PUMP -T TH_ PROGR _D DISCH-\G_ PR_SSUR_ (PID) S_TPOINT LOC-T_D IN R_GIST_R U1-01. ST-\T WITH Q5-03= 50PSI - -01=85PSI.

B.) I- TH_ SUCTION PR_SSUR_ DROPS B_LOW TH_ PROGR _D S_TPOINT IN Q5-03, TH_ V- ILL LOW_R TH_ SP__D TO M-INT-IN TH_ PROGR _D SUCTION PR_SSUR_ R_SULTING IN _CR_ _ IN DISCH-VG_ PR-SSURE. THE SETPOINT LOC-TED IN REGISTER Q5-08 EST- ISHES THE MINIMUM SPEED R_QUIR_D BY TH_ PUMP TO _NSUR_ - . ST- T WITH Q5-08= 40HZ. WH_N TH_ SUCTION PR_SSUR_ RIS_S _ TH_ PROGR _D S_TPOINT IN Q5-06, - \ LONG_R TH- TH_ TIM_ PROGR _D IN Q5-07, NORM- ISCH-\G_ PR_SSUR_ R_GUL-TION WILL R_SUM_. ST-\T WITH Q5-06= 50PSI - ,5-07= 2 S_C.

C.) I- TH_ SUCTION PR_SSUR_ DROPS B_LOW TH_ PROGR __D MINIMUM SUCTION PR_SSUR_ S_TPOINT LOC-T_D IN R_GIST_R Q5-04, - \ LONG_R TH- TH_ TIM_ S_T IN Q5-05, TH_ PUMPING SYST_M WILL SHUT DOWN (SL__P). ST-\T WITH Q5-04= 30PSI - \5-05=5 S_C. WH_N TH_ SUCTION PR_SSUR_ RIS_S _ Q5-06 - \ LONG_R TH- TH_ TIM_ S_T IN Q5-07, NORM- ISCH-\G_ PR_SSUR_ R_GUL-TION WILL R_SUM_.

D.) - H = TH= S = - .-T= - ILITI=S TO - TOM-TIC- / - T=RN-T= PUMP OP_R-TION SH _ PROVID_D. THIS _-TUR_ M-' B_ DIS _D BY TH_ OP_R-TOR I _SIR_D.

L.) THE PUMPS SH ER-TE IN EX LE- / L -IGUR-TION - THE L-H-TR- K TH_ SP__D O- TH_ L_- .

-.) WHEN IN NORM- ISCH- VGL PRESSURE CONTROL, THE DRIVE(S) WILL SHUT DOWN (SLEEP) I- THE PR_SSUR_ ST-'S -T OR _ TH_ Q1-01 S_TPOINT WITH TH_ L _-ST _D - TH_ DRIV_ RUNNING -T MINIMUM PUMP SPILD. THE DRIVE WILL W-KE UP WHEN THE DISCH-VGE PRESSURE DROPS BY THE DI ERENTI ET IN P1-04. ST-VT WITH P1-04= -5PSI.

3.TH_ CONTR- TOR SH- I-1 TH_ T _S __C_SS-_Y TO OP_R-T_ IN TH_ M __R D_SCRIB_D - \OVID_ _T_ LISTING O _ _ _T_RS IN TH_ O&M M _ .

4.TH_ MODBUS CONN_CTIONS - VOM TH_ V- TO TH_ =XISTING SC - VTUS SH = UTILIZED TO PROVID_ TH_ - ING IN- M-TION - X =- H DRIVE: DISCH- VG_ PRESSURE SETPOINT, SUCTION PR_SSUR_ S_TPOINT, DISCH-\G_ PR_SSUR_, SUCTION PR_SSUR_, MOTOR RPM, MOTOR CURR_NT, L _D RUN TIM_, - T D_SCRIPTION. TH_ CONTR- TOR SH - IST TH_ CITY WITH TH_ R_QUIR_D MODBUS M- ING.

	No.	DAT-	R_VISIONS	D_S: RDK		HOWARD F. CURREN ADVAN
ROMAN D. KORCHAK, P.=. #42626 _L_CTRICAL S_CTION H_AD	3			DRN: RDK	CITY of TAMPA	Built
WAST_WAT_R D_PARTM_NT	2			CKD:	WASTEWATER DEPARTMENT	
	1			DAT_: 3/20/17	WASTEWATER DEFARIMENT	

TPB017-024


1.TH_ T _S ON THIS SH__T - _ PROVID_D - ID_ TO TH_ V- \OGR- ING R_QUIR_D TO OP_R-T_ TH_ PROPOSED BOOST_R PUMPS IN TH_ M _R D_SCRIBED BELOW. IT IS NOT PURPORTED TH-T THE T ES - VE COMPLETE OR ERROR-- VEL. THE CONTR- TOR SH E RESPONSIBLE - V D_T_RMINING - INST- ING TH_ CORR_CT P- \ _T_RS TO - ILIT-T_ TH_ - ING BOOST_R PUMP

> ICED WASTEWATER TREATMENT PLANT SCREEN & GRIT DING NOS. 1 & 2 BOOSTER PUMPS

W.O. 1000721 SH__T

E9

VFD PARAMETERS



2

-IL-N

CITY of TAMPA WASTEWATER DEPARTMENT

CKD:

DAT_: 3/20/17

PIPING AND

TPB017-025

KEYED NOTES

1 PROPOS_D BOOST_R PUMP
2 PROP. BOOST_R PUMP MOTOR
3 PROP. ADJUSTABL: - \=Q. DRIV:
(4) PROP. GAT_ VALV_
5 PROP. BALL VALV=
6 PROP. CH_CK VALV_
7 PROP.T
8 =XISTING SCADA RTU
PT PROP. PR_SSUR_ TRANSMITT_R
PG PROP. PR_SSUR_ GAG_
PI PROP. PR_SSUR_ INDICATOR
(\underbrace{M}) prop. Induction motor
— — — — <u>-</u> L_CT. VARIABL_ OR BINARY


1.) THE PID DIAGRAM SHOWN APPLIES TO BUILDING No.1. THE PID - 🔨 2.) THE BOOSTER PUMPS - \ BUILDING No.1 ARE DESIGNED TO INCREASE THE _ ENT WATER PRESSURE - \ THE ENTIRE --CILITY. THE BOOSTER PUMPS - \ BUILDING No.2 ARE DESIGNED TO INCREASE THE E ENT WATER PRESSURE TO ONLY THE SCREEN ROOM.

ED WASTEWATER TREATMENT PLANT SCREEN & GRIT NG NOS. I & 2 BOOSTER PUMPS	W.O. 1000721
INSTRUMENTATION DIAGRAM	SHT EIO

	VFD1 CONTROLS PARTS SCHEDULE (VFD2 SCHEDULE IS SIMILAR)										
ITEM	QUAN.	DESCRIPTION	RATINGS	MANUFACTURER	PART NUMBER	COMMENTS					
VFD1	1	IQPUMP100 NEMA 12	17.5 AMPS , 480 V	YASKAWA		W/ LINE & LOAD					
(VFD2)	T	VFD PACKAGE	17.5 Alvii 5 , 400 V			REACTORS					
MCB	1	MAIN CIRCUIT BREAKER	30 AMPS, 600 V	SQUARE D	HGL36030	35 kAIC @ 480 V					
						WITH PRIMARY AND					
CT1	1	CONTROL TRANSFORMER	240X480V-120V, 500 VA	SQUARE D	9070TF500D1	SECONDARY FUSE					
						BLOCKS					
	2	REJECTION CLASS CC FUSES	2 AMPS, 600 V	BUSSMANN	FNQ-R-2	FOR CT1 PRIMARY					
	1	MIDGET FUSE	6 AMPS, 250 V	EDISON	MEN-6	FOR CT1 SECONDARY					
		RED MUSHR'M HEAD P.B.			9001-SKR99H13	TAG- "PUSH TO STOP.					
PB-S	1	2-POS MAINTAINED	NEMA 4X	SQUARE D		PULL TO ENABLE"					
		CONTACT									
	3	PUSH TO TEST LED PILOT	NEMA 4X	SQUARE D	9001-SKT-38LRW9	TAGS AS SHOWN					
PL-1, PL-4, PL-5	3	LIGHT WITH WHITE LENS									
PL-2. PL-3. PL-6	3	PUSH TO TEST LED PILOT	NEMA 4X	SQUARE D	9001-SKT-38LRR9	TAGS AS SHOWN					
PL-2, PL-3, PL-0	5	LIGHT WITH RED LENS	NEIVIA 4X								
PL-7	1	PUSH TO TEST LED PILOT	NEMA 4X	SQUARE D	9001-SKT-38LRG9	TAG AS SHOWN					
FL-7	Т	LIGHT WITH GREEN LENS		SQUARE D	9001-3K1-30LK09						
CR1-CR5, ES1	6	4 POLE CONTROL RELAY	120 V COIL, 15A CONTACTS	SQUARE D	RPM42F7	WITH LED & PUSH TO					
	0	4 POLE CONTROL RELAT	120 V COL, 13A CONTACTS	JQUARE D	NF 10142F 7	TEST BUTTON					
	6	SOCKETS		SQUARE D	RPZF4						
	6	VARISTOR PROTECTION	110 - 240 VAC	SQUARE D	RXM021FP						
	0	MODULE	110-240 VAC	SQUARE D	NAIVIOZIEP						
PT1-D, PT1-S	2	PRESSURE TRANSMITTER	150PSI, 4-20mA, 2-WIRE	ASHCROFT	A2X-B-MO4-42-C2-150#-G	HAZARDOUS AREA					
(PT2-D, PT2-S)	Z	PRESSORE TRAINSIVILLER	130P31, 4-2011A, 2-991RE	ASHCKUFI	A2A-B-1004-42-C2-130#-G	CERTIF: CLASS I, Div. 1					
PI1-D, PI1-S		2	DIGITAL PROCESS METER	85 TO 265 VAC POWER	PRECISION DIGITAL	PD765-6XO-00	1.2" DISPLAY				
(PI2-D, PI2-S)	۷.		4-20 mA ANALOG INPUT	FRECISION DIGITAL	FD705-0AU-00	I.Z DISPLAY					

N-L-

	No.	DAT-	R_VISIONS	D_S: RDK	_	Howard F. Curren Advanced Wastewater Treatment Plant Screen & Grit	W.O. 1000721
ROMAN D. KORCHAK, P #42626	3			DRN: RDK	CITY of TAMPA	BUILDING NOS. 1 & 2 BOOSTER PUMPS	SHT
LL_CTRICAL S_CTION H_AD	-						
WASILWAILK DEPARTMENT	2			CKD:	WASTEWATER DEPARTMENT	VFD CONTROLS SCHEDULE	EII
	1			DAT_: 3/20/17			



KEYED NOTES:

(1) EXISTING ELECTRICAL ROOM (FLOOR ELEVATION +11'-6"). REFER TO SHEETS EX FOR WORK REQUIRED.


 $\langle 2 \rangle$ EXISTING SCREENING EQUIPMENT, NO WORK REQUIRED.

 $\begin{tabular}{|c|c|c|c|c|c|c|} \hline \hline (3) Location for proposed booster pumps (floor elevation +15'-6"). \end{tabular}$

DVANCED WASTEWATER TREATMENT PLANT SCREEN & GRIT	W.O. 100
BUILDING NOS. & 2 BOOSTER PUMPS	W.U. 100
Soleding Nos. 1 & 2 DOOSTER 1 OPPS	SHE

BUILDING No.2 FLOOR PLAN







PLOT

	CONDUIT & CONDUCTOR SCHEDULE								
TAG	SIZE	CONDUCTORS	FROM	TO	СОМ				
VFD1L1	1"C	(3) #8 AWG , (1) #10 GND	MCC28, 4E	VFD1	ХНН				
VFD1M1	1"C	(3) #8 AWG , (1) #10 GND	VFD1	WBP-1	ХНН				
VFD1C1	3/4"C	(2) #14 AWG, (1) #14 GND	LOCAL "ON-OFF" SWITCH	VFD1	ХНН				
VFD1N1	3/4"C	(2) 2C-#18-TP-SHIELDED	PRESS. TRANS PT1-S &	VFD1	BELD				
VEDINI	3/4 U	(1) #14 GND	PT1-D	VFDI	BELD				
VFD1SC	3/4"C	(1) CAT-5E	VFD1	EX. SCADA RTU					
VFD1SD	1"C	(10) #14 AWG, (1) #14 GND	VFD1	EX. SCADA RTU	ХНН				
VFD2L1	1"C	(3) #8 AWG , (1) #10 GND	MCC28, 8E	VFD2	ХНН				
VFD2M1	1"C	(3) #8 AWG , (1) #10 GND	VFD2	WBP-2	ХНН				
VFD2C1	3/4"C	(2) #14 AWG, (1) #14 GND	LOCAL "ON-OFF" SWITCH	VFD2	ХНН				
VFD2N1	3/4"C	(2) 2C-#18-TP-SHIELDED	PRESS. TRANS PT2-S &	VFD2	BELD				
VEDZINI	3/4 U	(1) #14 GND	PT2-D	VFDZ					
VFD2SC	3/4"C	(1) CAT-5E	VFD2	EX. SCADA RTU					
VFD2SD	1"C	(10) #14 AWG, (1) #14 GND	VFD2	EX. SCADA RTU	ХНН				

н		No.	DAT-	R_VISIONS	D_S: RDK		HOWARD F. CURREN ADVANCED
z	ROMAN D. KORCHAK, P.1. #42626 LI-CTRICAL SICTION HIAD	3			DRN: RDK	CITY of TAMPA	Building
-	WAST_WAT_R D_PARTM_NT	2			CKD:	WASTEWATER DEPARTMENT	BUILDING No.
		1			DAT_: 3/20/17	WA TEWATEN DELANIMENT	





MCC 21 PARTIAL ONE-LINE DIA.



- 11		No.	DAT-	R_VISIONS	D_S: RDK		Howard F. Curren Adva
- 11	ROMAN D. KORCHAK, P.1. #42626 LI-CTRICAL SICTION HIAD	3			DRN: RDK	$CITY \text{ of } TAMP_A$	Bui
÷	WAST_WAT_R D_PARTM_NT	2			CKD:	WASTEWATER DEPARTMENT	BUILDI
		1			DAT_: 3/20/17	WA TEWATEN DELANIMENT	

TPB017-029

vanced Wastewater Treatment Plant Screen & Grit uilding Nos. 1 & 2 Booster Pumps DING No. 2 , MCC-21 DETAILS